

# OCONEE COUNTY PROCUREMENT OFFICE

415 S. PINE ST., WALHALLA, SC 29691 Phone 864-638-4141 Fax 864-638-4142

## REQUEST FOR QUOTATION

### THIS IS NOT AN ORDER

- Please quote on this sheet in the spaces provided below.
- Vendors must state their delivery after receipt of order.
- Base quote on terms & conditions shown.
- Quote shall be valid for 30 days.
- Quotes are due back in this office by the deadline stated
- Prices shall include all freight charges to destination.

RETURN QUOTE TO:  
Robyn Courtright  
Email: rcourtright@oconeesc.com  
Fax: 864-638-4142

RFQ DATE: 1-12-2017

Do not proceed with anything on this request until you receive notification from the Oconee County Procurement Office and until a purchase order is issued.

### ALL BLANKS BELOW TO BE FILLED IN BY THE QUOTING VENDOR

Name of Company: \_\_\_\_\_ Quotation Date: \_\_\_\_\_ Quotation #: 16-104Q

Authorized Signature: \_\_\_\_\_ Print Signature: \_\_\_\_\_

Phone #: \_\_\_\_\_ Email: \_\_\_\_\_

<b>Return Quote By:</b>	<b>Deliver To:</b>	<b>Terms:</b>	<b>FOB:</b>
1-19-2017 @ 2:00pm	See specs.	Net 30	Destination, Freight Prepaid

Qty	Description	Unit Price	Total Price
1	Liebert Single Module UPS System		
	Per attached specifications		
	Shipping Charges:		

STATE YOUR DELIVERY DATE AFTER RECEIPT OF A PURCHASE ORDER: _____	SALES TAX (6%):	
	GRAND TOTAL:	

## MINIMUM SPECIFICATIONS

Oconee County is seeking quotations from qualified vendors to provide and deliver one (1) Liebert eXM Single Module UPS System to Oconee County FOCUS, Seneca Network Operations Center, 361 Market Street, Seneca, SC, 29678.

### Minimum Specifications

Liebert eXM Single Module UPS System consisting of the following:

- One (1) 40kVA Nameplate Liebert eXM UPS, model 47SA040EAC00 – NO EXCEPTIONS with the following features:
  - System Input Voltage of 208/120V, 3 Phase, 4 wire plus ground
  - System Output Voltage of 208/120V, 3 Phase, 4 wire plus ground
  - Fixed Capacity 40kVA UPS System
  - Single Input Configuration
  - One (1) IntelliSlot Unity Dual Protocol Card; P/N: IS-UNITY-DP; Offers a web interface to monitor and configure the Emerson Life.net and Emerson Network Power proprietary protocols for use with Liebert Nform and Emerson Trellis. It allows you to select and configure two of the available third party protocols – SNMP, Modbus or BACnet for interfacing to Liebert SiteScan or Building Management Systems.
  - One (1) IS-RELAY Relay Contact Card(s)
  - Transformer-Free Architecture - Efficiency up to 95% in double conversion mode
  - Unity Power Factor Rating - Delivers more usable power per kVA
  - Load Power Factor Support - Supports loads 0.5 lagging to unity without derating
  - Energy Optimization Mode (Eco-Mode)
  - 65kAIC Rating - Provides interrupting rating and labeling of 65kA
  - Active Power Factor Corrected IGBT Input Converter
  - PWM transistorized (IGBT) inverter
  - Continuous Duty Static Bypass Switch
  - Input Contacts - Dry contacts are available for functions including monitoring external breakers, on-generator signal, and other functions
  - Output Contacts - Dry contacts are available for functions including a permissive signal to maintenance bypass SKRU, to trip external breakers, and other functions
  - Generator Load Control - Suppresses battery charging reducing power demand by an external signal. Shifts unit from Eco Mode to double conversion (if applicable), and synchronizes the inverter output with the bypass
  - Automatic retransfer - Provides return to inverter power after an overload
  - DSP based controls - Provides digital control of power conversion and system operation
  - Backlit LCD display - Monitors power conversion, UPS operation and utility conditions.
  - Deviations are logged for troubleshooting
  - Temperature-Compensated Charging/Battery Load Test
  - Top-and-bottom-entry cable access
  - Front only service access
  - Local Emergency Power Off (EPO)
  - LIFE™ Services for the 1st year
  - IP 20 enclosure
  - Casters and leveling feet
  - UL and cUL Listed to UL Standard 1778 4th Edition
- One (1) Liebert eXM Battery Cabinet System model 47BPERX61L with the following features:
  - 18 min @ 40 kVA, 1 -600 MM External Cabinet of ENERSYS HX330-FR Batteries
  - 18 min: Run Time at Ordered KVA
  - BP-No Battery Monitoring
  - Cabinet Mounted Left Attached to Module
  - The battery is provided with a 3-year full and 7 year prorated warranty
- One (1) Maintenance Bypass Matching Cabinet, model 47MBE32CC0R with the following features:
  - 3 Switching Devices (BIB,MBB,MIB)
  - 175 Amp Breaker Trip Rating
  - Cabinet Mounted Right Attached to Module with connecting cables factory supplied
  - 200 MM - 7.9 inches Frame Size

- Front Access service design
- System Start-up Services - Start-up includes one site trip by a LS customer engineer after the UPS has been installed. The site trip includes the following services for one UPS module: non-powered inspection, UPS electrical and operational checkout, full parts and labor for any remedial work required on the UPS or battery cabinets, and customer operation training. Start-up also includes remedial onsite labor, parts, and travel for the full one-year warranty period. Startup 8x5 is scheduled Monday thru Friday - 8 am to 5 pm. MBC/BDC/Wallmount Panel Startup is included

### **Basis of Award**

The award of quote will be to the most responsible, responsive bidder based on low price. Oconee County reserves the right to reject any or all bids, waive any technicalities or informalities if it is deemed in the best interest of the County.

### **Delivery**

Quote price shall include delivery to Oconee County FOCUS Seneca Network Operations Center, 361 Market Street, Seneca, SC, 29678.